

SUPER SILENZIOSI

SERIE PROFESSIONAL
"OPEN"



EUROCOMPRESS
AIR COMPRESSORS



I Elettrocompressore supersilenzioso.
Funzionamento completamente automatico, completo di riduttore di pressione, filtro riduttore a richiesta, manometro pressione di utilizzo, manometro pressione serbatoio, interruttore on-off.
Motore con protezione termica.
Serbatoio di tipo CE (normativa CEE 87/404), protetto internamente con verniciatura antiossidazione (solo serbatoio lt. 24 - 25 - 50) e completo di rubinetto scarico condensa.

GB Supersilent electrocompressor.
Automatic function with pressure reducer, reducing pressure filter by request, manometer pressure use, manometer pressure tank, on-off switch.
Motor with thermal protection.
Tank type CE (norm CEE 87/404), internally protected with varnish antioxidantization (only tank lt. 24 - 25 - 50) and with discharged faucet condense.



Model PROFESSIONAL "OPEN"	AIR CE Tank	dB (A)	air displacement		F.A.D.		HP		voltage	Hz	bar	psi	cm. a x b x c	Kg. Lbs	
			lt/min	cfm	lt/min	cfm	HP	KW						Kg.	Lbs
9/50	9	40	50	1,8	37	1,3	0,5	0,35	230/50	8	114	32x32x53	21	46	
15/50	15	40	50	1,8	37	1,3	0,5	0,35	230/50	8	114	35x35x56	25	55	
24/50	24	40	50	1,8	37	1,3	0,5	0,35	230/50	8	114	40x40x61	28	62	
25/100 TA	25	40	100	3,6	74	2,6	0,5+0,5	0,35+0,35	230/50	8	114	58x32x58	41	90	
50/100 TA	50	40	100	3,6	74	2,6	0,5+0,5	0,35+0,35	230/50	8	114	98x44x65	55	121	

By request: Volt 230/60 Hz - Volt 115/60 Hz

EUROCOMPRESS
AIR COMPRESSORS

20090 Trezzano sul Naviglio (MI) ITALY - Via Brunelleschi, 16/20
Tel.: +39/02.44.54.656 - 02.44.50.027 - Fax: +39/02.44.50.027
<http://www.eurocompress.it> - E-mail: eurocompress@eurocompress.it

SUPER SILENZIOSI

SERIE PROFESSIONAL SERIE JUNIOR



EUROCOMPRESS
AIR COMPRESSORS



I Elettrocompressore supersilenzioso.
Funzionamento completamente automatico, completo di filtro riduttore di pressione e scarico condensa (mod. Junior), riduttore di pressione (mod. Professional), filtro riduttore a richiesta, manometro pressione di utilizzo, manometro pressione serbatoio, interruttore on-off.
Motore con protezione termica.
Serbatoio di tipo CE (normativa CEE 87/404), protetto internamente con verniciatura antiossidazione (solo serbatoio lt. 24 - 25 - 50) e completo di rubinetto scarico condensa.

GB Supersilent electrocompressor.
Automatic function, with reducing pressure filter and discharged condense (Junior model), pressure reducer (Professional model), reducing pressure filter by request, manometer pressure use, manometer pressure tank, on-off switch.
Motor with thermal protection.
Tank type CE (norm CEE 87/404), internally protected with varnish antioxidization (only tank lt. 24 - 25 - 50) and with discharged faucet condense.



Model JUNIOR	at 5 bar														
	Tank	dB (A)	air displacement lt/min cfm		F.A.D. lt/min cfm		HP KW		volt Hz		bar psi		cm. a x b x c		Kg. Lbs
4/30	4	40	30	1,1	21	0,75	0,25	0,20	230/50	8	114	39x18x45		15	33
6/30	6	40	30	1,1	21	0,75	0,25	0,20	230/50	8	114	39x18x48		16	35

Model PROFESSIONAL	at 5 bar														
	Tank	dB (A)	air displacement lt/min cfm		F.A.D. lt/min cfm		HP KW		volt Hz		bar psi		cm. a x b x c		Kg. Lbs
9/30	9	40	30	1,1	21	0,75	0,25	0,20	230/50	8	114	30x30x53		18	40
9/50	9	40	50	1,8	37	1,3	0,5	0,35	230/50	8	114	32x32x53		21	46
15/50	15	40	50	1,8	37	1,3	0,5	0,35	230/50	8	114	35x35x56		25	55
24/50	24	40	50	1,8	37	1,3	0,5	0,35	230/50	8	114	40x40x61		28	62
25/100 TA	25	40	100	3,6	74	2,6	0,5+0,5	0,35+0,35	230/50	8	114	58x32x58		41	90
50/100 TA	50	40	100	3,6	74	2,6	0,5+0,5	0,35+0,35	230/50	8	114	98x44x65		55	121

By request: Volt 230/60 Hz - Volt 115/60 Hz