

serie

Energy Export



EUROCOMPRESS[®]
AIR COMPRESSORS

DENTAL DIVISION

Energy Export



(GB) Dental air compressor oilless available with 24 and 50 lt. tank.

The main characteristics that distinguish this series are: absolutely automatic function, motor with thermal protection.

Tank type CE (norm CEE 87/404), internally protected with varnish antioxidization and with discharged faucet condense.

(ES) Dental compresor sin aceite disponible con tanque de 24 y 50 lt.

Las principale carateristicas que distinguen esta serie son: funciona automáticamente, motor con protección térmica.

El tanque cumple la normativa CE (CEE 87/404), y está protegido internamente con varniz antioxidante y con grifo de descarga de condensación.



at 5 bar

ENERGY Model	Units	AIR CE Tank	dB (A)	air displacement lt/min cfm	FAD. lt/min cfm	HP KW	volt Hz	type	cyl.	R.P.M.	bar psi	cm. a x b x c	kg. Lbs
24/100	1	24	70	100 3,5	65 2,3	0,75 0,55	230/50	GMS100	1	1400	8 114	41x40x64	26 57
24/100	1	24	70	125 4,4	72 2,6	0,75 0,55	115/60-230/60	GMS100	1	1700	8 114	41x40x64	26 57
24/114	1	24	70	105 3,7	65 2,3	1 0,75	230/50	F114	1	1400	8 114	41x40x64	25 55
24/114	1	24	70	130 4,6	72 2,6	1 0,75	115/60-230/60	F114	1	1700	8 114	41x40x64	25 55
24/150	1-2	24	75	150 5,3	121 4,3	1,5 1,1	230/50	GMS150	1	1400	8 114	41x40x63	31 68
24/150	1-2	24	75	180 6,3	135 4,8	1,5 1,1	115/60-230/60	GMS150	1	1700	8 114	41x40x63	31 68
24/150 V	2	24	68	200 7	125 4,4	1,5 1,1	230/50	EXTREME	2v	1400	8 114	41x43x60	31 68
24/150 V	2	24	68	250 8,6	140 5,0	1,5 1,1	115/60-230/60	EXTREME	2v	1700	8 114	41x43x60	31 68
24/200 V	2-3	24	75	200 7	150 5,3	2 1,5	230/50	VS 204	2v	1400	8 114	41x43x60	36 79
24/200 V	2-3	24	75	250 8,6	180 6,4	2 1,5	115/60-230/60	VS 204	2v	1700	8 114	41x43x60	36 79
24/230 V	3	24	68	250 8,8	180 6,4	2 1,5	230/50	EXTREME	2v	1400	8 114	41x43x61	33 72
24/230 V	3	24	68	280 9,9	200 7	2 1,5	230/60	EXTREME	2v	1700	8 114	41x43x61	33 72
50/150	1-2	50	75	150 5,3	121 4,3	1,5 1,1	230/50	GMS150	1	1400	8 114	46x43x94	40 88
50/150	1-2	50	75	180 6,3	135 4,8	1,5 1,1	115/60-230/60	GMS150	1	1700	8 114	46x43x94	40 88
50/150 V	2	50	68	200 7	125 4,4	1,5 1,1	230/50	EXTREME	2v	1400	8 114	46x43x91	40 88
50/150 V	2	50	68	250 8,8	140 5,0	1,5 1,1	115/60-230/60	EXTREME	2v	1700	8 114	46x43x91	40 88
50/200 V	2-3	50	75	200 7	150 5,3	2 1,5	230/50	VS 204	2v	1400	8 114	46x43x91	45 99
50/200 V	2-3	50	75	250 8,8	180 6,4	2 1,5	115/60-230/60	VS 204	2v	1700	8 114	46x43x91	45 99
50/230 V	3	50	68	250 8,8	180 6,4	2 1,5	230/50	EXTREME	2v	1400	8 114	46x43x92	42 92
50/230 V	3	50	68	280 9,9	200 7	2 1,5	230/60	EXTREME	2v	1700	8 114	46x43x92	42 92

EUROCOMPRESS

DENTAL DIVISION

20090 Trezzano sul Naviglio (MI) ITALY - Via Brunelleschi, 16/20
 Tel.: +39/02.44.54.656 - 02.44.50.027 - Fax: +39/02.44.50.027
<http://www.eurocompress.it> - E-mail: eurocompress@eurocompress.it